

Pneumatic Nailer Type W 15-358

The compact and well balanced stapler drives corrugated fasteners type W in lengths from 9 to 15 mm. It satisfied a multitude of fastening requirements and is the perfect solution when fastening butt and corner joints.



Popular applications:
Butt and corner jointing in furniture, windows and doors.

Length: 307 mm
Width: 70 mm
Height: 261 mm

Technical data

Type description:	W 15 - 358
Article code:	12000133
Magazine type :	Top loader
Safety:	Contact actuation
Fastener type:	Corrugated Fasteners Type W
Magazine capacity:	77
Fasteners per strip:	3 x 24
Operating pressure:	6 - 8 bar
Max. operating pressure:	8 bar
Air consumption/operation:	1.5 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 90 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 96 dB
Weight:	3 kg

The vibration as per ISO 8662-11 is 4.5m/s²

Extras supplied with the nailer: Operating instructions, spare parts list, service instructions, silencer

Subject to technical modifications.

Accessories:

Article code	Description
14403442	Mounting flange
14403402	Remote valve complete
14403409	Remote valve with safety yoke
14401023	Set for corner fastening
14405865	Piston, unit
14406593	Single actuation set

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.




This tool conforms to the EG Directive
for Machinery (98/37 EC)

Pneumatic Nailer Type W 15-358

Corrugated fasteners Type W



Joh. Friedrich Behrens AG
P.O.Box 14 80
22904 Ahrensburg /
Germany
Phone: +49 (0) 4102 78-0
Fax: +49 (0)4102 78-250
www.bea-group.com
e-mail: info@bea-group.com



Description	L = Length mm
W 09 BK A	09
W 12 BK A	12
W 15 BK A	15

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut